



# SCANSPEED Centrifuges

## 406G- Low-Speed Microcentrifuge



- Automatic alarm system for imbalance, over-heat and over-speed.

-Automatic door release.

- Supplied with an autoclavable fixed-angle rotor (for 6 X 15 ml) and 6 steel sleeves for 15 ml tubes.

-Program memory for up to 10 programs.

### A Rotor & Accessories for 406G



Fixed angle rotor, GAM-15-6  
6 tubes  
Angle : 45°  
Steel sleeves, GBT15  
Sleeve bore  $\phi$  : 18 mm

Tube					
Tube capacity (ml)	15	3	5	10	15 ml Conical
Adapter	None			None	None
Adapter $\phi$ x L (mm)	-	13 x 63	13 x 85	-	-
Max. rpm	4,000				
Max. rcf (g-force)	2,075	1,703	1,986	2,057	2,003
Radius (mm)	116	95.5	111	115	112



- ① FND display (speed / remaining run time)
- ② "Set" keys
- ③ Function selection keys

### Technical Specifications

	406G
Max. RPM	4,000 rpm
Max. RCF	2,075 x g
Max. capacity	15 ml x 6
Run time	≤ 99 min 59 sec or continuous
Acceleration time	≤ 20 sec
Deceleration time	≤ 20 sec
Program memory	10
Power & Frequency	220 V (110 V optional), 50-60 Hz
Dimension (W x D x H) mm	296 x 412 x 206
Weight without rotor	17.5 Kg

Please contact our sales representative or visit websites, [www.genehk.com](http://www.genehk.com) and [www.labogene.com](http://www.labogene.com) for detailed information.